#### (12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

### (19) World Intellectual Property Organization

International Bureau



## - 1881 | 1881 | 1881 | 1881 | 1881 | 1881 | 1881 | 1881 | 1881 | 1881 | 1881 | 1881 | 1881 | 1881 | 1881 | 1881

(43) International Publication Date 4 August 2005 (04.08.2005)

**PCT** 

# (10) International Publication Number WO 2005/071709 A2

(51) International Patent Classification7:

H01J 37/15

(21) International Application Number:

PCT/EP2004/014180

(22) International Filing Date:

13 December 2004 (13.12.2004)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

04001222.1


21 January 2004 (21.01.2004) E

(71) Applicant (for all designated States except US): ICT INTEGRATED CIRCUIT TESTING GESELLSCHAFT FÜR HALBLEITERPRÜFTECHNIK MBH [DE/DE]; Ammerthalstrasse 20a, 85551 Heimstetten (DE).

- (72) Inventor; and
- (75) Inventor/Applicant (for US only): FROSIEN, Juergen [DE/DE]; Kufsteinerstr. 16a, 88521 Riemerling (DE).
- (74) Agents: ZIMMERMANN, Gerd et al.; Zimmermann & Partner, P.O. Box 330 920, 80069 Munich (DE).
- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL. IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM,

[Continued on next page]

(54) Title: BEAM OPTICAL COMPONENT HAVING A CHARGED PARTICLE LENS



(57) Abstract: The present invention relates to a beam optical component including a charged particle lens (1; 1000) for focusing a charged particle beam (3), the charged particle lens (1; 1000) comprising a first element (5; 1005) having a first opening (7) for focusing the charged particle beam (3); a second element (9; 1009) having a second opening (11) for focusing the charged particle beam (3); and first driving means (13) connected with at least one of the first element (5; 1005) and the second element (9; 1009) for aligning the first opening (7) with respect to the second opening (11). With the first driving means, the first opening (7) and the second opening (11) can be aligned with respect to each other during beam operation to provide a superior alignment of the beam optical component for a better beam focussing. The present invention also relates to a charged particle beam device that uses said beam optical component for focussing the charged particle beam (3), and a method to align first opening (7) and second opening (11) with respect to each

## WO 2005/071709 A2



ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

### Published:

 without international search report and to be republished upon receipt of that report